

# PERFORMANCE DATA SHEET

Model: Smart Choice SCWF3CT0™ Water & Ice Refrigerator Replacement Filter for PureSource 3, PureSource Ultra

## APPLICATION GUIDELINES / CONDITIONS OF USE

<b>Water Supply</b>	Municipal or well applications
<b>Water Temp.</b>	Max. 100°F (38°C), Min. 33°F (0.6°C)– For cold water use only
<b>Water Pressure</b>	100 psi (689 kPa) Max. 30 psi (207 kPa) Min., as measured at the valve inlet

- Timely cartridge replacement is essential for the product to perform as advertised. Please refer to the Use & Care Manual for general operation and maintenance requirements. Your refrigerator has an electronic light on the freezer door dispenser that lights up yellow or displays **ORDER** when it is almost time to replace the filter and lights up red or displays **REPLACE** when you must replace the filter. Press the indicator button for approximately 3-10 seconds to reset after replacing the filter cartridge. Please refer to the Use & Care Manual for complete instructions. Flush the new cartridge for 4 minutes.
- Do not use the **Smart Choice SCWF3CT0** on water microbiologically unsafe or with water of unknown quality without adequate disinfection before or after the system. You may use the system on disinfected waters that may contain filterable cysts.
- While testing was performed under standard laboratory conditions, actual performance may vary. High sediment areas may require you to replace the filter cartridge more frequently. Spent absorption media will not be regenerated or used.
- The **Smart Choice SCWF3CT0** will absorb bad tastes and odors in both ice cubes and drinking water.

## SYSTEM SPECIFICATIONS


<b>Flow Rate</b>	Ice Maker - 3.4 to 4.3 oz (99 - 125 cc) per 6.3 seconds at 60 psi (as measured at valve inlet) Dispenser - 60 oz per minute (0.5 gpm or 1.9 liters per minute) at 60 psi (as measured at valve inlet)
<b>Capacity</b>	200 gallons (757 liters)
<b>System Construction</b>	Filter Housing Assembly - Polypropylene Plastic Water Storage Tank - Polyethylene Plastic Tubing - Polyethylene Plastic Filter Media - Extruded Carbon Block

## REPLACEMENT CARTRIDGE INFORMATION

Replacement **SCWF3CT0** cartridges are available through your local Frigidaire dealer or by calling the Customer Assistance Center at 1-800-374-4432. Please reference **INSTALLATION** in the Use & Care Manual for replacing the cartridge and warranty information. Estimated cost for the replacement filter cartridge kit: Less than \$40.00.

## PERFORMANCE DATA

**MODEL: Smart Choice SCWF3CT0** Use the replacement cartridge listed below.

	The <b>Smart Choice SCWF3CT0</b> cartridge has been tested according to NSF/ANSI Standard 42 for the reduction of substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 42.
---	--

**General test water parameters:** pH = 7.5 +/- 0.5 Temp. 20°C +/- 3°C (68°F +/- 5°F) Pressure = 60 psi

Substance Reduction	NSF Standard	NSF Reduction Requirements	Influent Challenge Concentration	Maximum Permissible Product Water Concentration	Average Percent Reduction
Chlorine taste and odor	42	>/= 50%	2.0 ± 10% mg/L	n/a	97.40%
Particulate class III	42	>/= 85%	Min. 10,000 part./mL	>/= 85%	99.90%





This filter is certified by the Water Quality Association to WQA/ASPE/ANSI-803 for sustainability.

Ce filtre est certifié par la Water Quality Association conformément à la norme WQA/ASPE/ANSI-803 pour la durabilité.

Este filtro está certificado por la Water Quality Association según WQA/ASPE/ANSI-803 por sostenibilidad.