


PERFORMANCE DATA SHEET

Model: Smart Choice SCWFTCT01™ Water & Ice Refrigerator Replacement Filter for PureSource Ultra® II

APPLICATION GUIDELINES / CONDITIONS OF USE	
Water Supply	Potable Water
Water Temp.	Max. 100°F (38°C), Min. 33°F (0.6°C)
Water Pressure	30 - 100 psi (206.8 - 689.5 kPa)
Service Flow	0.65 gpm maximum (2.46 lpm)
<ul style="list-style-type: none"> It is essential the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See Installation Manual for Warranty information. While testing was performed under standard laboratory conditions, actual performance may vary. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 42. Spent adsorption media will not be regenerated and used. The compounds certified under NSF 401 have been deemed as "emerging compounds/incidental contaminants. Emerging compounds/incidental contaminants are those compounds that have been detected in drinking water supplies at trace levels. While occurring at only trace levels, these compounds can affect the public acceptance/perception of drinking water quality. 	

REPLACEMENT CARTRIDGE INFORMATION	
Replacement Element: SCWFTCT01. For estimated cost of replacement elements please call 1-800-374-4432 or visit us on the web at Frigidaire.com	
PERFORMANCE DATA	
MODEL: Smart Choice. Use the replacement cartridge SCWFTCT01.	
	System tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of substances listed below.
SYSTEM SPECIFICATIONS	
Capacity	200 gallons (757 liters)

WARNING

Read entire manual. Failure to follow all guides and rules could cause personal injury or property damage.

Check with your local public works department for plumbing codes. You must follow their guidelines as you install the Water Filtration system. Your Water Filtration system will withstand up to 100 pounds per square inch (psi) water pressure.

To reduce the risk associated with choking:
DO NOT allow children under 3 years of age to have access to small parts during the installation of this product.

To reduce the risk associated with the ingestion of contaminants:
DO NOT use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after use of the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

CAUTION

To reduce the risk associated with property damage due to water leakage or flooding:

- Read and follow Use Instructions before installation and use of this system.
- Change the disposable filter cartridge at the recommended interval; the disposable filter cartridge **MUST** be replaced every 6 months or sooner.
- Failure to replace the disposable filter cartridge at recommended intervals may lead to reduced filter performance and failure of the filter, causing property damage from water leakage or flooding.
- Installation and use **MUST** comply with all state and local plumbing codes.
- Protect from freezing, remove filter cartridge when temperatures are expected to drop below 33° F (4.4° C).
- DO NOT install systems in areas where ambient temperatures may go above 110° F (43.3° C).
- DO NOT install on hot water supply lines. The maximum operating water temperature of this filter system is 100°F (37.8°C).

Substance Reduction	Average Influent	NSF/ANSI Specified Challenge Concentration	Average % Reduction/ Minimum Reduction	Average Product Water Concentration	Maximum Permissible Concentration	NSF Reduction Requirements	NSF Test Report
Chlorine	2.0 mg/L	2.0 mg/L ± 10%	>97.4%	0.05 mg/L	N/A	≥ 50%	J-00297278
Nominal Particulate Class III	4,600,000 pts/mL	At least 10,000 particles/mL	99.3 / 99.0%	38,000 pts/ml		≥85%	J-00297279

Contaminant reduction determined by NSF testing.





This filter is certified by the Water Quality Association to
WQA/ASPE/ANSI-803 for sustainability.

Ce filtre est certifié par la Water Quality Association conformément à
la norme WQA/ASPE/ANSI-803 pour la durabilité.

Este filtro está certificado por la Water Quality Association según
WQA/ASPE/ANSI-803 por sostenibilidad.