

# Freestanding Range

FGIF3061NF



## Signature Features



### Faster Boiling with Induction

Finish meals faster with our induction technology, including four elements that are more responsive than gas and electric ranges bringing water to a boil in two minutes.




### Reduce Cleanup Time

Our induction cooktop reduces cleanup time. It heats the pan, not the cooktop — so spills can't burn on.



### Quick Preheat

Preheat in just a few minutes.<sup>1</sup>



### True Convection

Single convection fan circulates hot air throughout the oven for faster and more even multi-rack baking.

## 30" Induction

### Product Dimensions

Height (Max.)	47-3/4"
Width	29-7/8"
Depth (Including Handles)	30"

### More Easy-To-Use Features

#### Quick Clean

Our one-touch self-cleaning button gives you a clean oven — fast.

#### Smudge-Proof™ Stainless Steel

Reduces fingerprints and smudges so it's easy to clean.

#### Effortless™ Temperature Probe with Auto Keep Warm

Take the guesswork out of cooking with the Effortless™ Temperature Probe that shows you the internal cooking temperature of your food instantaneously. You can set the desired finished temperature and the oven alerts you when that temperature has been reached. The oven then holds the desired temperature of the meat by switching to a keep warm function for better cooking results.

#### Keep Warm Zone

Keep food warm until everything — and everyone — is ready.

#### Built with American Pride

Appliances that are high-performing, more accessible, and more innovative than ever — designed, built, and engineered in the U.S.A.

Sabbath Mode (Star-K® Certified)

Available in:




Stainless  
(F)

Elements	Size	Watts
Right Front	Induction 10"	2,600/3,800
Right Rear	Induction 5"	800/1,000
Left Front	Induction 7"	1,920/2,640
Left Rear	Induction 6"	1,450/1,900
Center	Keep Warm Zone	100

<sup>1</sup>Based on single rack cooking performance, not set temperature, using Quick Preheat.

<b>Features</b>	
Oven Control/Timing System	Precision Set™
Surface Type	Black Ceramic Glass
Window	Picture
Exterior Door Finish	Smudge-Proof™ Stainless Steel
Handle Design	Stainless Steel
Exterior Finish (Side Panels)	Black
Convection System	True Convection
Oven Cleaning System	Self Clean
Drawer Functionality	Storage
<b>Oven Controls</b>	
Bake/Broil	Yes/Variable (400 - 500 °F)
Effortless™ Convection Conversion	Yes
Convection Bake/Broil/Roast	Yes/No/Yes
Quick Bake Convection	
Quick Preheat	Yes
Effortless™ Temperature Probe	Yes
My Favorite	
Chicken Nugget Button	
Pizza Button	
Keep Warm	Yes
Add-a-Minute	
Delay Start	Yes
Self Clean	Yes
Quick Clean Option	Yes
Delay Clean	2, 3, 4 Hours
Kitchen Timer / Timed Cook Option	Yes/Yes
Auto Oven Shut-Off	6 Hours
Oven Lock-Out	Yes
Lower Drawer Control	
<b>Cooktop Features</b>	
Right Front Element (Watts)	Induction 10" - 2,600/3,800
Right Rear Element (Watts)	Induction 5" - 800/1,000
Left Front Element (Watts)	Induction 7" - 1,920/2,640
Left Rear Element (Watts)	Induction 6" - 1,450/1,900
Center Element (Watts)	Keep Warm Zone - 100
<b>Oven Features</b>	
Capacity (Cu. Ft.)	5.4
Oven Light	1
Hidden Bake Element	Yes
Rack Configuration	2 Heavy Duty, 1 Effortless™
Baking System	Even Baking Technology
Broiling System	Vari-Broil™
Bake Element/Broil Element (Watts)	3,500/3,900
Drawer Racks	
<b>Certifications</b>	
Sabbath Mode (Star-K® Cert.)	Yes
<b>Specifications</b>	
Oven Interior (H x W x D)	19-3/4" x 24-3/8" x 19-1/8"
Power Supply Connection Location	Middle Bottom Rear
Voltage Rating	240V / 208V / 60Hz
Connected Load (kW Rating) @ 240 / 208 Volts	15.5 / 12.0
Amps @ 240 Volts	40 Amps
Minimum Circuit Required (Amps)	40
Shipping Weight (Approx.)	220 Lbs.




*NOTE: For planning purposes only. Always consult local and national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at [frigidaire.com](http://frigidaire.com).*



Product Dimensions	
A - Height (Max.)	47-3/4"
B - Width	29-7/8"
C - Depth (Including Handle)	30"
Depth with Door Open 90°	49"

Cutout Dimensions	
Height (Stand.)	36"
Width (Min.)	30"
Depth (Min.)	24"

*Accessories information available on the web at [frigidaire.com](http://frigidaire.com)*



**\*Note:** 30" minimum clearance between top of cooking surface and bottom of unprotected wood or metal overhead cabinet; or 24" minimum clearance when bottom of wood or metal overhead cabinet is protected by not less than 1/4" flame-retardant millboard covered with not less than No. 28 MSG sheet steel, 0.015" stainless steel, 0.024" aluminum or 0.020" copper. 0" clearance is minimum for rear of range. Follow all dimension requirements provided above to prevent property damage, potential fire hazard, and incorrect countertop and cabinet cuts.

**Freestanding Range Specifications**

- Product Shipping Weight (approx.) - 220 Lbs.
- Single phase 3- or 4-wire cable, 120/240 or 120/208 Volt, 60 Hertz, fused on both sides of line with ground.
- Connected Load (kW Rating) @ 240/208 Volts = 15.5/12.0kW
- Recommended Circuit Breaker - 40 Amps
- Always consult local and national electric codes.
- Make sure wall coverings around range can withstand heat generated by range.
- Floor beneath range MUST be solid and level.
- Overhead cabinetry should not exceed a 13" maximum depth.
- Absolute minimum horizontal distance between overhead cabinets installed to either side of appliance must be no less than maximum width of appliance.
- Range can be installed flush to wall with 0" minimum rear clearance.
- Minimum 1" clearance required from edge of rangetop to nearest combustible wall on either side of range above 36" height.

- Allow 30" minimum clearance between top of cooking surface and bottom of unprotected wood or metal overhead cabinet; or 24" minimum clearance when bottom of wood or metal overhead cabinet is protected by not less than 1/4" flame retardant millboard covered with not less than No. 28 MSG sheet steel, 0.015" stainless steel, 0.024" aluminum or 0.020" copper.
- To reduce risk of fire when using overhead cabinetry, install range hood that projects horizontally a recommended minimum of 5" beyond bottom of cabinets.
- Follow all dimension requirements provided to prevent property damage, potential fire hazard, and incorrect countertop and cabinet cuts.

**Note:** For planning purposes only. Refer to Product Installation Guide on the web at [frigidaire.com](http://frigidaire.com) for detailed instructions.

