



50 Pint Dehumidifier

Dehumidifier

Available Products: FHDD5033Y1

Available Colors: White

Version: 02/26

Product Specifications

Dehumidifier

Air CFM (Low)	197 CFM
Air CFM (High)	218 CFM
Fan Speeds - Fan	2
Noise Level dBA (Low)	49 dBA
Noise Level dBA (High)	51.5 dBA
Motor RPM (Low)	1090 RPM
Motor RPM (High)	1190 RPM
Air Discharge	Top of Unit
Container Full Indication	Yes
Digital Humidity Readout	Yes
Dust Air Filter	Yes
Filter Access Location	Rear
Filter Check Indicator	Yes
Low Temperature Operation	Yes
Option for Advanced Filtration	No
Pump Feature	No

Functions

24-Hour On/Off Timer	Yes
Auto Restart	Yes
Auto Shut-Off	Yes
Continuous Drain Operation	Yes

Dimensions and Volume

Height	19 1/10"
Width	18 9/10"
Depth	9 9/10"

Installation

Power Cord Length	72"
-------------------	-----

Connectivity

Wi-Fi Enabled	Yes
---------------	-----

Safety Certifications and Approvals

cUL Listed	Yes
UL Listed	Yes

Performance

Bucket Capacity	1.9 Gallons
Dehumidification - Pints per Day	50
Relative Humidity Minimum	35 %
Relative Humidity Maximum	85 %
Integrated Energy Factor (L/kWh)	2.01

Controls

Control Type	Electronic
--------------	------------

Electrical Specifications

Amps	8.8 Amps
Voltage Rating	115 V
Watts	470 Watts

General Specifications

Prop 65 Label	Yes
Refrigerant Type	R-32
Warranty - Labor	1 Year
Warranty - Parts	1 Year

Performance Certifications and Approvals

Energy Efficiency Verification (Canada)	Yes
ENERGY STAR Certified	Yes

Accessories Sold Separately

PureAir Filter	No
----------------	----