



High Humidity 50 Pint Capacity Dehumidifier with Built In Pump

Dehumidifier

Available Products: FFAP5033W1

Available Colors: White

Version: 02/23

Product Specifications

Dehumidifier

Air CFM (Low)	167 CFM
Air CFM (Med)	194 CFM
Air CFM (High)	229 CFM
Fan Speeds - Fan	3
Noise Level dBA (Low)	47 dBA
Noise Level dBA (Med)	49 dBA
Noise Level dBA (High)	51 dBA
Motor RPM (Low)	880 RPM
Motor RPM (Med)	980 RPM
Motor RPM (High)	1,160 RPM
Air Discharge	Top of Unit
Container Capacity	16.9 pints
Container Full Indication	Yes
Digital Humidity Readout	Yes
Filter Access Location	Back
Filter Check Indicator	Yes
Low Temperature Operation	Yes
Option for Advanced Filtration	No
Pump Feature	Yes
Quick Glance Light	No

Functions

24-Hour On/Off Timer	Yes
Auto Restart	Yes
Auto Shut-Off	Yes
Clean Air Ionizer	No
Continuous Drain Operation	Yes

Dimensions and Volume

Height	24 3/4"
Width	16"
Depth	12 1/4"

Installation

Power Cord Length	78"
-------------------	-----

Performance Certifications and Approvals

Energy Efficiency Verification (Canada)	Yes
ENERGY STAR Certified	Yes

Performance

Bucket Capacity	2.1 Gallons
Dehumidification - Pints per Day	50
Relative Humidity Minimum	35 %
Relative Humidity Maximum	85 %
Integrated Energy Factor (L/kWh)	1.8

Controls

Child Lock	No
Control Type	Electronic

Electrical Specifications

Amps @ 120 Volts	7.8 Amps
Plug Type	LCIDI 5-15P
Voltage Rating	115 V
Watts @ 120 Volts	545 Watts

General Specifications

Prop 65 Label	Yes
Refrigerant Type	R-410A
Warranty - Labor	1 Year
Warranty - Parts	1 Year

Connectivity

Wi-Fi Enabled	No
---------------	----

Safety Certifications and Approvals

UL Listed	Yes
cUL Listed	Yes