

High-Efficiency Laundry Centre FFLE39C1QW

4.4 Cu.Ft. Washer
5.5 Cu.Ft. Dryer
Electric



Product Dimensions

Height	77"
Width	27"
Depth	31-1/2"

More Easy To Use Features

Timed Dry Cycle

Select your desired drying time limit that works with your schedule.

Available in:



Classic
White
(W)

¹Based upon an estimated 5 lbs. of laundry per day for a family of three. Actual load weight may vary with a maximum of 15 lbs. per load.

Signature Features

Super Capacity

Fit more in every load. Wash and dry 3 days of laundry at once with our 4.4 cu.ft. HETL washer¹.

Super Efficiency

Strong, efficient cleaning performance, every time, with our high efficiency washer with stainless steel tub.

8 Wash Cycles


Features 8 multiple wash cycles to meet all of your washing needs such as delicate, bedding and casual.

4 Drying Cycles

Offers 4 drying cycles to meet all of your drying needs including Delicates, Casuals and Heavy-Duty.

Washer Features	
Washer Type	HE Top Load
Total Capacity (Cu.Ft.)	4.4
Controls	Ready-Select®
Washer Interior	Stainless Steel
Vibration Control System	Yes
Suspension System	
Wash System	
Fresh Water Rinse	Yes
Automatic Temperature Control	
Water Level Adjustments	3
Bleach Dispenser/Detergent Dispenser	Yes/No
Fabric Softener Dispenser	
Cycle Signal	
Cycle Signal "On/Off"	
Agitate Speeds (Strokes/Min.)	Variable
Spin Speeds (RPM)	850
Wash Cycles	
Wash Cycles/Specialty Cycles	8/0
Washer Options	
Temperature Selections	3 (Rotary)
Water Levels	3
Energy Saver Option	
Dryer Features	
Total Capacity (Cu.Ft.)	5.5
Dryer Drum Interior	Stainless Steel
Interior Light	
Wrinkle Release Technology	
DrySense™ Technology	
Moisture Sensor	
Cycle Signal	
Cycle Signal "On/Off"	
Tumble Speed (RPM)	50
Lint Screen	Yes
Dry Cycles	
Dry Cycles/Specialty Cycles	4/0
Dryer Options	
Temperature Selections	3
Dryness Level Selections	0
Timed Dry (Minutes)	15, 30, 45, 90
Optional Accessories	
Mobile Home Installation Kit	PN# 137067200
Drying Rack	PN# DRLC
Specifications	
Maximum Exhaust Duct Length¹ (Ft.)	56
Power Supply Connection Location	Middle Rear
Water Inlet Connection Location	Middle Rear
Voltage Rating	240V/60Hz/30A
Connected Load (kW Rating) @ 240 Volts	5.1
Amps @ 240 Volts	22
Heating Element @ 240 Volts (Watts)	4,500
Shipping Weight (Approx.)	275 Lbs.

¹Rigid metal duct preferred, semi-rigid optional and allow deductions for elbows and vents. Refer to Installation Guide on web for additional information.



NOTE: For planning purposes only. Always consult local and national electric and plumbing codes. Refer to Product Installation Guide on the web at frigidaire.ca for detailed installation instructions.



Product Dimensions	
A - Height	77"
B - Width	27"
C - Depth	31-1/2"
Depth with Door Open 90°	47-1/2"

Accessories information available on the web at frigidaire.ca